



Above glass awning

markilux 770 tracfix

The clean and concise exterior awning for medium-sized areas.



reddot design award
winner 2017



markilux.com

0800 953 0199

www.aqblinds.co.uk

markilux
safe timeless beautiful


Product Characteristics

Wind resistance class 3
Beaufort 6 → 38–48 km/h → 10.5–13.4 m/s → 24–30 mph



1 side view
track-only fixture

2 when extended, the front profile finishes flush
with the end of the guide tracks



3 tracfix cover guidance system – leaves no gap between
the cover and the guide track



Product Characteristics

Description

- exterior awning for conservatories and glass canopies. One awning can shade an area of up to 18 m²

Special features

- fully encompassing cassette that protects the cover perfectly
- tried and tested tensioning system with drive belts and integrated gas pistons – delivers optimum cover tension in any phase of extension
- with tracfix system, the continuous lateral cover guidance system that leaves no gap between the cover and guide tracks – gives improved wind stability and a cleaner appearance
- the broad range of brackets with patented clip-on system offers individual fixture solutions

Dimensions

- single unit: awning fixture width 60–450 cm in width, maximum extension 400 cm
- maximum dimensions, awning fixture width × extension: 450 cm × 400 cm
- intermediate sizes are available

Roller tube and lateral bearings

- round roller tube Ø 85 mm with keyway, galvanised steel – excellent stability, ensures near perfect cover performance even at the largest widths
- the roller tube bearing is made of stainless steel

Awning profiles

- extruded aluminium, in façade quality, powder coated
- cassette profile in two pieces, angular, height × depth 125 mm × 125 mm
- guide tracks angular, rounded edges, width × height 52 mm × 52 mm
- front profile rounded at the front, depth × height 110 mm × 52 mm

End caps

- the cassette end caps are made of die-cast aluminium, in two parts, powder coated
- the front profile end caps are made of high-quality plastic, powder coated

Fixture brackets

- extruded aluminium, powder coated
- cassette is self-supporting on guide tracks
- brackets for the guide tracks: stand-off brackets, reveal fixture, flat track brackets for lateral fixture
- standard bracket heights: 105 mm / 145 mm / 100–500 mm (bespoke heights can be ordered)
- other accessories are available

Frame colours

markilux frame colours without surcharge

traffic white, RAL 9016



metallic aluminium, RAL 9006



grey brown, similar to RAL 8019



off-white textured finish, 5233 ¹⁾



stone grey metallic, 5215 ¹⁾



anthracite metallic, 5204 ¹⁾



havana brown textured finish, 5229 ¹⁾



Non-standard powder-coated finish

Bespoke frame colours incur a surcharge – matt, metallic, finely textured and pearl finishes as well as other colour ranges (DB, Tiger etc.) on request. All frame colours are available at a surcharge with enhanced corrosion protection.

Colours may differ slightly from those depicted in both hue and finish.

¹⁾ textured finish


Dimensions and configuration options


Single unit


Order dimensions		Awning fixture width							Minimum fixture width	
		150	200	250	300	350	400	450	Hard-wired motor	Radio-controlled motor
		72	151	201	251	301	351	401		
		150	200	250	300	350	400	450		
		+ 5,4								
H	150								72	82
	200									
	250									
	300									
	350								107 ¹⁾	107 ¹⁾
	400									
dimensions in cm										

1) = from an extension of 281 cm

H = extension

 = 4 brackets

 = 6 brackets

 = 6 brackets,
1 cover support tube

Operation	standard	optional
crank handle	—	—
hard-wired motor	✓	—
silentec motor (optionally with an external io / RTS receiver)	—	—
radio-controlled motor io, 868 MHz	—	✓
radio-controlled motor RTS, 433 MHz	—	✓
868 MHz radio-controlled motor io with manual override	—	—

Coupled awnings

not available

Optional accessories

automatic controls (light, wind, rain)

N.B. Important background information can be found in the chapter "Optional Accessories"

Awning cover	fabric pattern no.	standard	optional
sunvas	300..–315..	✓	—
sunsilk	324.. / 325.. / 328.. / 369..	✓	—
sunbow	411..–427..	✓	—
smart art	340..	—	✓
perla FR	371.. / 372..	—	✓
perfotex	331.. / 332..	✓	—
transolair	338..	—	✓
transolair (120 cm)	339..	—	✓
vuscreen Alu	317..	—	✓
Soltis Perform 92	92–..	—	✓

Shadeplus

not available

sunvas
transolair
perla FR

Fabric pattern 301.. / 309.. – 315..
339..
371..³⁾ / 372..³⁾

smart art
sunsilk

340..
324.. / 325.. / 328.. / 369..

Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

sunvas

Fabric pattern 31008..¹⁾, -09¹⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300				1)	1)	1)	
	350				1)	1)	1)	
	400				1)	1)		

1) also available in fabric width 320 cm – then seamless





sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints
 (panel width approx. 120 cm)
  = seamless
  = not available
  = horizontal panel joint(s)
 AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Serge 600 (not available) Fabric pattern 272..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Soltis Perform 92 Fabric pattern 277..
Fabric width 177 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	180							
	250							
	300							
	350							
	400							


Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

= horizontal panel joint(s)

dimensions in cm


Fixtures, fittings and accessories



track bracket, with adjustable head

100 mm


76046.



double track bracket with adjustable head 100 mm

central bracket for 2 single units next to each other


73634.



track bracket for conservatory transom fixture

100 mm


76055.



windmill track bracket

100 mm


76054.



track bracket with offset footplate

100 mm


76199.



track bracket for track-only fixture, rigid


100 mm

76017.




track bracket for track-only fixture, rigid by the metre, undrilled, 100 mm maximum length 6 mm

76013.



track bracket, with adjustable head 140 mm


76048.



double track bracket with adjustable head 140 mm

central bracket for 2 single units next to each other


73636.



track bracket, with adjustable head and foot

200-500 mm


76045.



track bracket, with adjustable head

140-500 mm


76047.



universal track bracket with adjustable head


140-500 mm

76053.



flat track bracket with adjustable head
for lateral guide track fixture


76049.



covering cap for square track bracket
standard accessory for bracket

2 x 76718.


Fixtures, fittings and accessories



spacer plate
for track bracket

110 × 40 × 10 mm


78570.



adapter plate
for track bracket

110 × 60 × 10 mm


78158.



adapter plate
for track bracket


110 × 60 × 10 mm

78165.



angled mounting
bracket


76098.



angled mounting
bracket 76098.


including coupling bolts

76099.



fixture bracket for light
and / or wind and/or
rain sensor

76050.




bracket for sun and/or
wind sensor io

76723.

Fixture types


21

Clearance 105 mm




22

Clearance 145 mm



30

Flat track bracket






Individual bracket selection:

See “Fixtures, fittings and accessories”.
Awning extension > 300 cm, always
3 brackets per guide track.

Overview of dimensions

Fixture type 21,22

Fixture type 30




		fixture type 21	fixture type 22	fixture type 30
HT	= bracket	76046.	76048.	76049.
HH	= bracket height	105	145	ca. 195–335
GH	= overall height	157	197	ca. 247–387
MA	= order dimension = blind fixture width = fixture width			
*	= extension when retracted			



dimensions in mm

Overview of dimensions

Single unit



Two single units – fixture via double track brackets




- * = extension when retracted
- H = **order dimension** = extension
- HH = bracket height
- M = awning width
- MA = **order dimension** = blind fixture width = fixture width
- SF = visible cover

dimensions in mm

Dimension overview Fixture type 21, 22


Fixtures, fittings and accessories



track bracket, with
adjustable head

100 mm


76046.



double track bracket
with adjustable head
100 mm


central bracket for 2
single units next to
each other

73634.



track bracket, with
adjustable head
140 mm


76048.



double track bracket
with adjustable head
140 mm

central bracket for 2
single units next to
each other

73636.




- 76019.** = bracket for cover support tube
BW = width between fixture points on the conservatory
H = **order dimension** = extension
HH = bracket height
HT = bracket
M = awning width
MA = **order dimension** = blind fixture width = fixture width

dimensions in mm

Dimension overview fixture combination 30


Fixtures, fittings and accessories



flat track bracket
with adjustable head

for lateral guide track
fixture

76049.



H = order dimension = extension
MA = order dimension = blind fixture width = fixture width
V1, V2, V3 = variants

dimensions in mm

Dimension overview eaves fixture with additional bracket fitting

Fixtures, fittings and accessories

track bracket accessory
width 14 mm


for direct assembly on
conservatory rafters

76804.

track bracket accessory
width 25 mm


for direct assembly on
conservatory rafters

76805.



dimensions in mm

Motor cable exit point



- * = extension when retracted
- = standard
- = optional
- = optionally with surcharge

dimensions in mm

01

02

03

04

05

06

07

08

09

10

11

12

13

14

■ **15**

16

17

18

19